

INPUT	
Voltage	208 - 220 V three-phase + N
Voltage tolerance	+ 15% - 20%
Frequency tolerance	45 to 65 Hz
Power factor	0.99
Current distortion	≤ 3% THDi

BY PASS	
Rated voltage	208 - 220 V three-phase + N
Voltage tolerance	-10% to + 15% (Ph-N) V
Rated frequency	60 Hz
Frequency tolerance	±6% (selectable)

OUTPUT and INVERTER OUTPUT	
Rated power	10000 VA
Active power	9000 W
Output Voltage	208 - 220 V three-phase + N
Dynamic stability	± 3%
Frequency	60 Hz
Frequency on battery operation	0.01%
Voltage distortion with non-linear load	≤ 3%
Voltage distortion with linear load	≤ 1%
Overload	103% infinite, 110% for 60 min, 125% for 10 min, 150% for 1 min

BATTERIES	
Type	VRLA AGM/GEL; NiCd

ENVIRONMENTAL	
Color	Pantone Black C
Communication	UPS status led bar; Graphic touch screen display; 2 slots for communications interface USB; RS232; Contact interface with 5x opto insulated Input and 4x Output relay
Safety compliance	UL 1778 5th Edition CSA C22.2 107.3 -05 and Annex NNN; UL 60950-11; FCC Part 15 Subpart J class A – IEC 62040-3
Operating temperature	0 °C / + 40 °C
Relative humidity	5% - 95% without condensing
Transport	Castors; Pallet Jack

DATA	
Weight	324 lb / 147 kg
Dimensions (h w d)	59.0 x 21.7 x 32.7 inches / 1500 x 550 x 830 mm