

INPUT	
Rated power	10000 VA
Voltage	208 / 220 / 230 / 240 V
Voltage tolerance	110 V <Vin <300 V @ 60% LOAD / 176 V <Vin <300 V @ 100% Load
Frequency	50 Hz/ 60 Hz
Frequency tolerance	60 Hz ± 5%
Power factor	>0.98
Current distortion	≤6%

BY PASS	
Voltage tolerance	176 / 276 V
Frequency tolerance	Frequency selected (from ±0 Hz to ±5Hz configurable)
Number phases	1

OUTPUT and INVERTER OUTPUT	
Rated power	10000 VA
Active power	10000 W
Number phases	1
Crest factor (I _{peak} /I _{rms})	3:1
Waveform	Sinewave
Frequency	Can be selected: 60 Hz or self-learning
Voltage distortion with non-linear load	≤4%
Voltage distortion with linear load	≤2%

OVERLOAD TIMES	
100% < Load < 110%	10 min.
Load > 130%	1 min.
125% = Load < 150%	1 min.

BATTERIES	
Type	VRLA AGM lead, maintenance-free
Typical recharge time	6 h

ENVIRONMENTAL	
Altitude max	6000 m
Color	Black
Communication	USB / DB9 with RS232 and contacts / Slot for communication interface
Safety compliance	UL1778:2014 and CSA C22.2 No. 107.3-14
EMC compliance	CFR 47 FCC Part 15, Subpart B, Class A 2016
Accessories provided	Power cable, serial cable, USB cable, safety manual, quick start, software downloadable
Protection rating	IP20
Surge capability	660 joule
Marks	Certified by TUV per UL 1778
Line-Interactive/Smart Active efficiency	98%
Noise	<40 dB(A) at 3.3 ft / 1 m
Operating temperature	32 – 104 °F / 0 – 40 °C
Relative humidity	<95% without condensation

DATA	
Weight	20 kg
Dimensions (h w d)	610x87x438 mm